

RTCUCX1 warp mk2 series

Advanced Telematics and Telemetry Appliance

The perfect balance of quality, performance, flexibility and affordability

For Professional M2M Applications

The RTCUCX1 warp mk2 series has been designed for the most demanding M2M and Internet of Things applications, which cannot be solved with simpler non-programmable devices.

The RTCUCX1 warp mk2 series rests on the **X32 architecture**, that brings all the necessary tools together to develop, implement and maintain today's sophisticated M2M/IoT applications.

The **development task** is supported by the **free** RTCUC IDE development environment complemented by a large and comprehensive documentation and application example library.

The RTCUC Gateway 2 is the corner-stone of the **communication infrastructure** ensuring reliable two-way device communication in any network environment.

Deploying and maintaining new application and firmware versions for devices in the field are handled by the powerful

Almost two decades of know-how in one product!

Experience and Know-how

For almost twenty years Logic IO has been committed to offer the most sophisticated platform for advanced and highly demanding M2M / IoT applications.

The RTCUCX1 warp mk2 series is the result of this accumulated experience combined with valuable feedback from hundreds of professional and mission critical applications by major organizations around the world.

RTCUC products are deployed **underground, stationary, on the road, at sea, on the rail and in the skies!** - In any imaginable application and environment.



Device Series Advantages

- Penta-band UMTS/HSPA engine.
- Multi-GNSS positioning engine.
- Large memory capacity.
- FAT32 file-system.
- Internal SIM reader.
- 3-axis accelerometer.
- Full CAN 2.0B support.
- 1-Wire bus.
- ISM medium range RF.
- RS232.
- Digital and analog I/O.
- Back-up battery.
- State of the art power-management.
- IP66 ruggedized encapsulation.
- Ready to use with interface cable!

Platform Advantages

- X32 execution architecture.
- Free RTCUC IDE development tool.
- Fully programmable.
- Huge standard API.
- Comprehensive protocol support.
- Full featured Device Simulator.
- Sophisticated deployment tools.
- Fast and free email support.
- Backward and forward compatible.

RTCU CX1 warp mk2 series Highlights

Advanced Telematics and Telemetry Appliance

The RTCU CX1 warp mk2 series is targeting a broad range of advanced telemetry / telematics applications and has been designed according to the highest technical standards for professional automotive and industrial use.

- Based on the **RTCU M2M Platform**.
- **X32 execution architecture.**
 - RTCU IDE development tool with full featured device simulator.
 - Huge standard API with more than 800+ functions.
 - Comprehensive protocol support, including:
TCP-UDP/IP, FTP, SMTP, RACP, MQTT, FMS/J1939, Garmin FMI.
- Penta-band **world-wide UMTS/HSPA engine**. Backward compatible with 2G/2.5G.
- Internal SIM-card reader.
- State-of-the art **Multi-GNSS positioning engine** with GPS, GLONASS, QZSS.
- High-performance **3-axis accelerometer** with 16g scale.
- Large data-flash/logger memory with a capacity **up to 4.5 MB**.
- Internal **4 MB FAT32 flash drive**.
- **1 x digital inputs** and **1 x high-power solid-state digital output** (upgradeable).
- Wide operating range from **8..36 VDC**.
- On-board **Li-Ion battery**.
- Advanced **power-management** with wake-up on a wide range of events.
- High-speed **Mini-USB programming** connector.
- Support the **Garmin Fleet Management Interface**.
- Fully supported by the **RTCU Gateway 2** and the **RTCU Deployment Server**.
- Available in two powerful hardware versions:
 - CX1 warp 3G** (RS232/1-wire)
 - CX1 warp-c 3G** (CAN)
- **Ruggedized IP66** plastic encapsulation.
- Delivered with a 50 cm interface cable.
- **Powerful on-demand hardware options:**
 - I/O:** **2 x digital inputs, 2 x digital outputs and 1 x analog input (total).**
 - RF:** **Medium range ISM band RF transceiver with on-board antenna.**
 - FLASH:** **Micro-SD card reader and 3 MB extended flash.**
 - COM:** **RS232/FMI and 1-Wire bus (warp) or CAN (warp-c).**
- **On-demand options** can be applied **anytime** — even remotely after installation.



Services Available

Technical Support.
Application development support.
Maintenance.
Hardware support.
Warranty services.

Accessories

On-demand hardware options.
RF accessories.
Antennas.
Cable parts.
1-Wire parts.
Industrial SD-CARD.
...and more.



Find out more and start developing today!

Learn more about the RTCU M2M platform and the NX32 architecture in the "The RTCU M2M Platform" data sheet.

To learn more about the technical details and usage of the RTCU CX1 warp series, please download the "RTCU CX1 warp series Technical Manual".

Also make sure to get the **FREE RTCU IDE** Development Environment, **RTCU Gateway 2** and the **Deployment Server** to get a hands-on experience how rapid development/deployment of game changing M2M/IoT applications were meant to be.

Please visit www.logicio.com

RTCX1 warp mk2 series Specifications

Processor and Main-memory

- Powerful 32-bit ST ARM7 processor.
- 1088 KB fast execution RAM.
- 2304 KB Flash for firmware/application.

Storage

- 3.5 MB persistent data flash.
- 4 MB internal FAT32 flash drive.
- 1 MB circular automatic datalogger.
- 8 KB Virtual FRAM with fast access / unlimited write endurance.
- Micro SD-CARD reader. Up to 32 GB.

GSM/UMTS

- Penta-band UMTS/HSPA.
GSM: 850/900/1800/1900 MHz.
UMTS: 800/850/900/1900/2100 Mhz.
- CSD with up to 14.4 Kbps.
- SMS / PDU.
- eCall Accident / Emergency services.
- Mini-SIM 1.8/3 volt.
- Internal SIM card-reader.

GNSS / GPS

- Mediatek MT3333 Multi-GNSS chip.
- GPS, GLONASS and QZSS.
- 99 acquisition / 33 tracking channels.
- SBAS (WAAS,EGNOS,MSAS,GAGAN).
- Position update with up to 4 hz.
- A-GPS capable.
- Sensitivity.
Tracking: -165 dBm
Reacquisition: -160 dBm
Cold start: -148 dBm.
- Accuracy: < 2.5m CEP.
- Anti-jamming, Noise cancellation.

Battery and Charger

- On-board 900mA (nom.) Li-Ion battery.
- Intelligent charger with temperature throttle and sub-zero degrees support.
- On-board temperature sensor.

Electrical Specification.

- Operating voltage is 8 to 36 VDC.
- Short and reverse power protected.

Digital/Analog Interface

- 2 x digital solid-state digital output.
Max. 36 volt / 0.75 A per. channel.
Short-circuit, ESD, Inductive kick-back protected up to 20 mH.
- 2 x digital inputs.
Logic high: 8 to 40 VDC.
Logic low: -5 to 3 VDC.
- Digital input #1 can be used as ignition.
- 1 x analog input.
Range is 0..10V.
Resolution: 10 bit
Precision: ±1.5% FSR @ 25°C

Communication

- **Warp-c:** Full CAN2.0B with hardware filtering and multi-speed support.
- **Warp:** RS232 and 1-Wire bus.
- On-board 868 Mhz ISM RF
Up to 15 meter indoor /
Up to 50 meter outdoor.

Power Management

- 5 execution speeds.
- Wait for Event: Timer, Digital input, RS232, CAN, GSM, Accelerometer and power change state.
- Wait for event, from: 600 uA@12V.
- Supervision of supply voltage / type.

Accelerometer

- 3-axis digital accelerometer.
- Resolution: 12 bit @ ±16g.
- Low-power mode.

Internal Interface

- Mini-USB connector for service port.
- Mini-SIM card-reader.
- Micro SD-CARD slot.
- Reset/recovery switch,

External Interface

- 2 x bi-color LED indicators.
- Yellow LED for status.
- SMA female connector for GSM antenna.
- SMA female connector for GPS antenna.

On-Demand Hardware Options

- Applied "any-time" - locally or remotely.
- Over-the-air hardware upgrade.

Physical Characteristics

- Encapsulation: Black UL94 plastic.
- Sealing membrane.
- 50 cm open-ended interface cable.
- Approx. 250 gram without accessories.
- W 92 x H 30 x D 58 mm.
(without mounting flanges).

Environmental Specification

- Operating temperature: -30 to 55°C.
- Battery charge temperature:
-10 to 45 °C
- Recommended storage temperature:
0 to 45 °C.
- Humidity: 5..90% (non condensing).
- IP-66 ingress protected.

Approvals

- E1 type approval:
2004/104/EC UN ECE R10.
- RE Directive, RED 2014/53/EU.
- RoHS.
- Cellular engine: CE/GCF/FCC/PTCRB.

Warranty

- Two-years return to factory parts and labor.
- Optional warranty up to 5 years.
(restrictions apply).

Logic IO Worldwide Headquarters

Holmboes Allé 14
8700 Horsens
Denmark
Phone: +45 7625 0210
Fax: +45 7625 0211
Commercial enquiries: sales@logicio.com
Technical support: support@logicio.com
www.logicio.com

Models Available

SKU: RT-CX1W3
SKU: RT-CX1WC3